

Non-metallic conduit systems

Type A & C90 - Adaptaseal

Type A - Adaptaseal

Straight fitting - Fixed external male thread / Materials: Polyamide (nylon) 66 /
Colour: Black (BL), Grey (GR)

	Part no.	Nominal conduit size (mm)	Metric thread		Part no.	Nominal conduit size (mm)	PG thread
	ASF10/M16/A	10	M16		ASF10/PG9/A	10	PG9
	ASF13/M16/A	13	M16		ASF13/PG9/A	13	PG9
	ASF16/M16/A	16	M16		ASF16/PG11/A	16	PG11
	ASF16/M20/A	16	M20		ASF16/PG13/A	16	PG13,5
	ASF21/M20/A	21	M20		ASF21/PG16/A	21	PG16
	ASC21/M20/A	21	M20		ASC21/PG16/A	21	PG16
	ASF28/M25/A	28	M25		ASF28/PG21/A	28	PG21
	ASC28/M25/A	28	M25		ASC28/PG21/A	28	PG21
	ASF34/M32/A	34	M32		ASF34/PG29/A	34	PG29
	ASC34/M32/A	34	M32		ASC34/PG29/A	34	PG29
	ASC42/M40/A	42	M40		ASC42/PG36/A	42	PG36
	ASC54/M50/A	54	M50		ASC54/PG48/A	54	PG48

For insertion into knockouts using a locknut. Locknut supplied with METRIC THREAD ONLY

To order quote part number & body colour, e.g. ASF10/M16/A/BL

PF & NPT thread sizes available

Approvals



IP rating

Appropriate conduit

For use with: Type PA / CP / PR / PF

IP66 Yes

IP67 Yes

IP68 Yes (2 bar 30mins)

IP69 Yes

Temperature range

Static applications: -40°C to +120°C

Moving applications: -5°C to +120°C

Type C90 - Adaptaseal

90° Elbow fitting - Fixed external male thread / Materials: Polyamide (nylon) 66 /
Colour: Black (BL), Grey (GR)

	Part no.	Nominal conduit size (mm)	Metric thread		Part no.	Nominal conduit size (mm)	PG Thread
	ASF10/M16/C90	10	M16		ASF10/PG9/C90	10	PG9
	ASF13/M16/C90	13	M16		ASF13/PG9/C90	13	PG9
	ASF16/M16/C90	16	M16		ASF16/PG11/C90	16	PG11
	ASF16/M20/C90	16	M20		ASF16/PG13/C90	16	PG13,5
	ASF21/M20/C90	21	M20		ASF21/PG16/C90	21	PG16
	ASC21/M20/C90	21	M20		ASC21/PG16/C90	21	PG16
	ASF28/M25/C90	28	M25		ASF28/PG21/C90	28	PG21
	ASC28/M25/C90	28	M25		ASC28/PG21/C90	28	PG21
	ASF34/M32/C90	34	M32		ASF34/PG29/C90	34	PG29
	ASC34/M32/C90	34	M32		ASC34/PG29/C90	34	PG29
	ASC42/M40/C90	42	M40		ASC42/PG36/C90	42	PG36
	ASC54/M50/C90	54	M50		ASC54/PG48/C90	54	PG48

For insertion into knockouts using a locknut. Locknut supplied with METRIC THREAD ONLY

To order quote part number & body colour, e.g. ASF10/M16/C90/BL

PF & NPT thread sizes available

Approvals



IP rating

Appropriate conduit

For use with: Type PA / CP / PR / PF

IP66 Yes

IP67 Yes

IP68 Yes (2 bar 30mins)

IP69 Yes

Temperature range

Static applications: -40°C to +120°C

Moving applications: -5°C to +120°C