

Cat No.	Description	Inner Carton	Outer Carton
<b>13 Amp Unswitched Socket Outlets</b>			
WP23	1 gang 13 amp, unswitched	-	10
WP23L	Large housing 1 gang 13 amp socket	-	10
WP24	2 gang 13 amp, unswitched	-	10



- IP66 Rated with plug in use, cover sealed
- Terminal capacity 3 x 2.5mm<sup>2</sup>, 3 x 4.0mm<sup>2</sup> & 2 x 6.0mm<sup>2</sup>
- Supplied with multiple knock-out mounting box
- 13A sockets manufactured to BS 1363-2



#### RCD Protected 13A Socket

WP22RCD | 2 gang 13 amp RCD, switched (latching)



- IP66 Rated with plug in use, cover sealed
- RCD sockets manufactured to BS 7288
- 30 milli-amp trip current, 40 milli-second trip speed
- Terminal capacity 3 x 2.5mm<sup>2</sup>, 3 x 4.0mm<sup>2</sup> & 2 x 6.0mm<sup>2</sup>
- Supplied with multiple knock-out mounting box

There are 2 types of RCD - **Latching** and **Non-Latching**; also termed active and passive. Both types are accepted by British Standards and it is up to the user to choose the type of RCD most suitable for their application.

**NON-LATCHING (active) RCDs** switch off when the power to them is turned off. Every time supply to the RCD is interrupted it will trip and will need to be reset.

**LATCHING (passive) RCDs** "remember" the state they were in prior to the power being switched off.

#### Time Controlled 13A Socket

WP23TM24 | Time controlled 1 gang 13 amp socket



- IP66 Rated with plug in use, cover sealed
- Socket manufactured to BS 1363-2
- 24 hour mechanical timer, 1 segment = 15 minutes. With override switch and LED power indicator
- Terminal capacity 3 x 2.5mm<sup>2</sup>, 3 x 4.0mm<sup>2</sup> & 2 x 6.0mm<sup>2</sup>
- Supplied with multiple knock-out mounting box