

| Cat No.                | Description                                        | Inner Carton | Outer Carton |
|------------------------|----------------------------------------------------|--------------|--------------|
| <b>Flex Connectors</b> |                                                    |              |              |
| 452                    | 10A, 3-pin shrouded non-reversible male and female | 20pks        | 200pks       |
| 458                    | 13A, 3-pin solid brass block through terminals     | 20pks        | 200pks       |



- Manufactured to BS 5733
- 2 plastic cable restraints retained by plated-steel slotted head screws
- Brass slotted head terminal screws

| Cat No.                 | Description | Pack Quantity | Inner Carton | Outer Carton |
|-------------------------|-------------|---------------|--------------|--------------|
| <b>Connector Strips</b> |             |               |              |              |
| TS2.5/12/10             | 2.5A 12 way | 10            | -            | 100pks       |
| TS5/12/10               | 5A 12 way   | 10            | -            | 100pks       |
| TS15/12/10              | 15A 12 way  | 10            | -            | 50pks        |
| TS30/12/10              | 30A 12 way  | 10            | -            | 30pks        |
| TS60/12/10              | 60A 12 way  | 10            | -            | 20pks        |

- Manufactured from thermoplastic
- Unique 'snap-off' spine design
- Maximum continuous temperature rating 80°C
- Nominal voltage 400V
- Fully backed-out screws to speed installations
- Manufactured to BS EN 60998-2-1



| Cat No.                   | Description  | Colour | Pack Quantity | Inner Carton | Outer Carton |
|---------------------------|--------------|--------|---------------|--------------|--------------|
| <b>Compression Glands</b> |              |        |               |              |              |
| CGND20B/10                | 7-10mm Ø20mm | Black  | 10            | 20pks        | 200pks       |
| CGND20W/10                | 7-10mm Ø20mm | White  | 10            | 20pks        | 200pks       |
| CGND20R/10                | 7-10mm Ø20mm | Red    | 10            | 20pks        | 200pks       |
| CGND25B/10                | 8-13mm Ø25mm | Black  | 10            | 20pks        | 200pks       |
| CGND25W/10                | 8-13mm Ø25mm | White  | 10            | 20pks        | 200pks       |
| CGND25R/10                | 8-13mm Ø25mm | Red    | 10            | 20pks        | 200pks       |



- UL + VDE Approved
- IP68 rated
- Temperature resistance -35°C to +80°C
- Dome Top
- For use with unarmoured cable
- Includes locknut & washer
- High mechanical strength strain relief