

LOW VOLTAGE MINIATURE FUSE-LINKS

TYPE MIN

200/240 Volt miniature Fuse-Links generally to IEC127

Rated voltage: 250V a.c. Rated breaking capacity: Various.

Current ratings and principal dimensions

DIMENSION MM	OPERATING CHARACTERISTIC	BODY MATERIAL	TYPE REF	RATING		FUSE- HOLDER TYPE	CARTON QUANTITY
				mA	AMPS		
5 X 20	FAST	GLASS	PDC	32, 40, 50, 63, 80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10, 15	KP	100 (10x10)
		CERAMIC	PCC	32, 40, 50, 63, 80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3.15, 4, 5, 6, 3, 8, 10		
	SLOW	GLASS	PDC-S	32, 40, 50, 63, 80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3.15, 4, 5, 6, 3, 8, 10		
		CERAMIC	PCC-S	125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
	ULTRA-FAST		PCC-UR		1.6, 2, 3, 15, 4, 5, 8, 10		
6.3 X 32	FAST	GLASS	KDC	10, 32, 40, 63, 100, 125, 150, 175, 187, 200, 250, 300, 375, 500, 600, 750	1, 1.25, 1.5, 1.6, 2, 2.5, 3, 4, 5, 6, 7, 8, 10	K	
		CERAMIC	KCC	125, 250, 375, 500, 750	1, 2, 3, 4, 5, 6, 7, 8, 10, 12, 15, 20, 25, 30		
	SLOW	GLASS	KDC-S	10, 32, 40, 63, 100, 125, 150, 175, 187, 200, 250, 300, 375, 400, 500, 600, 700, 750, 800	5, 6, 7, 8, 20, 25, 30		
	SLOW	CERAMIC	KCC-S	10, 32, 63, 100, 125, 150, 175, 187, 200, 250, 300, 375, 400, 500, 600, 700, 750, 800	1, 1.25, 1.5, 1.6, 2, 2.5, 3, 4, 5, 6, 7, 8, 10, 12, 15, 20, 25, 30		
			KCC-UR		1, 1.25, 2, 3, 4, 5, 6, 7, 8, 10, 12, 15, 20, 25, 30		
5 X 25	FAST	GLASS	TDC	80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
		CERAMIC C/W INDICATOR	TCC		1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
		GLASS	TDC-M	80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10		
		CERAMIC C/W INDICATOR	TCC-M	80, 100, 125, 160, 200, 250, 315, 400, 500, 630, 800	1, 1.25, 1.6, 2, 2.5, 3, 15, 4, 5, 6, 3, 8, 10,		



Lawson Type "MIN" fuse-links are available to meet a wide variety of applications. Miniature and other small dimensioned fuse-links are grouped into several different application categories and comply with different specifications. Many different types are available with current ratings from 10mA to 30 Amps.

