



Order Code: 84D US5 W

Sheer Floor Satin Steel 1 gang 5A
Unswitched Socket. Standard Insert will be
White.

Attributes

Primary Range Sheer Floor Insrt US5
Plate material Metal Size (single) height 86mm Size (single) width 86mm

Size (single) depth 3.0mm (6.5mm Hinged Cover)

Box fixing hole centres 60.3mm Minimum wall box depth 35mm Current rating 5 Amp 220/250V AC Voltage Max load 5 Amp IP rating IP2XD Switched Poles none Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed **Ambient Operating** -5° to +40°C Temperature Recommended Location Indoor use only

2000m

BS 546

Max installation Altitude

BS EN ISO Standard

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. NSSPlus





R. Hamilton & Co Ltd.

Unit G

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

Tel: +44 (0)1747 860088

Fax: +44 (0)1747 861032

Email: info@hamilton-litestat.com

Web: www.hamilton-litestat.com