430268 | Technical Specification

Drivers

Multi Dim Driver (Push Dim, 1-10v & DALI2) 8W - 22W 200-550mA 30-40VDC

Multi Dim Driver (Push Dim, 1-10v & DALI2) 8W - 22W 200-550mA 30-40VDC

General Data

Technology	CC | AC | SELV
Electrical Connector Type	Push Terminal
Input Cable	0.75-2.5mm²
Input Electrical Connection	Live | Neutral
General Application	Commercial | Residential | Educational
Operating Temperature Range °C	-10 - +40
Warranty (Years)	5

© 2025 Lumineux Lighting. Part of B&T Associates Limited. Registered in England, Company Number 01987654.

430268	Technical Specification

Electrical Data

Wattage (W)	8 - 22
Mains voltage (V)	220 - 240
Lamp power factor	>90
Electrical protection	Class II
Driver Output (V)	30 - 40
Driver Output Current (mA)	200 - 550
Control Gear Type CC or CV	Constant Current
Dimmable	Yes
Dimmable Type	1-10
Recommended Dimmers	DALI
Inrush Current (A)	15.1
Nominal Frequency (Hz)	50 | 60
Surge Protection (kV)	L-N:0.5
Max. Luminaire per 10A C Breaker	34
Max. Luminaire per 13A C Breaker	44
Max. Luminaire per 16A C Breaker	55
Max. Luminaire per 20A C Breaker	68
Max. Luminaire per 10A B Breaker	21
Max. Luminaire per 13A B Breaker	27
Max. Luminaire per 16A B Breaker	33
Max. Luminaire per 20A B Breaker	41

© 2025 Lumineux Lighting. Part of B&T Associates Limited. Registered in England, Company Number 01987654.

430268	Technical Specification

Physical Data

Housing Colour	White
Body Material	ABS
IP Rating	20
Nominal Product Length (mm)	143
Nominal Product Width (mm)	58
Nominal Product Height (mm)	30
Weight (kg)	0.13

© 2025 Lumineux Lighting. Part of B&T Associates Limited. Registered in England, Company Number 01987654.