


Amenity

Hawkridge Dual Wattage 18W & 28W Wall Pack 3CCT Black



Tough Aluminium body with Polycarbonate diffuser, LED lifespan 50,000 hours L70, Standard, Emergency and Dusk to Dawn options available, IK10 Impact rated, Selectable wattages



General Data

Technology	LED
Mounting options	Surface-Mounted
Install Options	Rear Entry 2x20mm Side Entry Points
Electrical Connector Type	4 Way Push Terminal
Input Cable	No
Input Electrical Connection	Live Neutral Earth
General Application	Residential Commercial
Operating Temperature Range °C	-20 - +40
Warranty (Years)	5

430698

Technical Specification

Optical Data

LED Manufacturer / Type	Huayuan
Fixture Luminous Flux (Lm)	1975 3075
Luminaire Efficacy @3000K (lm/W)	110
Luminaire Efficacy @4000K (lm/W)	110
Luminaire Efficacy @6000K (lm/W)	110
LOR %	100
Colour Selectable	Yes
Beam Angle°	Asymmetric
Optics	Type IV
Photobiological Risk Group	RG0

Light Source Data

Energy Class	C
Lumens	2906 4314
Lm/W	160
Colour Temperature (K)	3000 4000 6000
Light Colour	Warm Light Cool White Daylight
CRI Ra	80

Electrical Data

Wattage (W)	18 28
Total power consumption (W)	17.9 28
Mains voltage (V)	220 - 240
Lamp power factor	>90
Electrical protection	Class I
Driver Output (V)	90
Driver Output Current (mA)	300
Control Gear Type CC or CV	Constant Current
SVM	2.05
PstLM	0.1
LED Flicker Rate	55
Dimmable	No
Driver Brand	Luminaireux
Inrush Current (A)	<19
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50 60
Surge Protection (kV)	1
Max. Luminaire per 10A C Breaker	56
Max. Luminaire per 13A C Breaker	72
Max. Luminaire per 16A C Breaker	89
Max. Luminaire per 20A C Breaker	111
Max. Luminaire per 10A B Breaker	33

430698

Technical Specification

Max. Luminaire per 13A B Breaker	43
-----------------------------------------	----

Max. Luminaire per 16A B Breaker	53
-----------------------------------------	----

Max. Luminaire per 20A B Breaker	67
-----------------------------------------	----

Lifetime Data

Lifespan L70 B50 @25°C (Hrs)	50000
-------------------------------------	-------

Physical Data

Housing Colour	Black Grey RAL 7021
-----------------------	---------------------

Body Material	Aluminium Die Cast
----------------------	--------------------

Driver Housing	Polycarbonate
-----------------------	---------------

IP Rating	65
------------------	----

IK Rating	08
------------------	----

Diffuser Material	Polycarbonate
--------------------------	---------------

Diffuser Finish	Clear
------------------------	-------

Nominal Product Length (mm)	264
------------------------------------	-----

Nominal Product Width (mm)	321
-----------------------------------	-----

Nominal Product Height (mm)	165
------------------------------------	-----

Weight (kg)	1.87
--------------------	------

430698

Technical Specification

Standards and Approvals

Manufactured In Accordance To	EN 60598-1
CE Mark	Yes
UKCA Mark	Yes
WEEE Symbol	Yes
Certificate of Conformity	Available on Request
Accredited Members	LIA, ISO9001

