

# Safe Isolation and Voltage Indication

## VT25

**Voltage range:** 12-690V AC/DC  
**Frequency range DC:** 16-400Hz  
**LED indication:** ±12, 24, 50, 120, 230, 400, 690V  
**Single Pole Phase Test:** 100-690V  
**Frequency range DC:** 50-60Hz  
**Phase Rotation Test:** 120-400V  
**Frequency range DC:** 50-60Hz  
**Continuity Range:** 0-500kΩ  
**GS38 caps:** removable  
**Standard & Regulations:**  
 BS EN 61243-3 2010  
**Cable length:** 1.2m  
**IP rating:** IP64  
**Auto power off**  
**Torch light:** White LED  
**Power:** 2 x 1.5V AAA  
**Weight:** 130g (with batteries)  
**Dimensions:** 205 x 67 x 27mm  
**Includes:** battery and manual

## Two Pole Voltage Tester

The VT25 is a compact voltage tester which measures continuity, phase rotation and voltages between 12V and 690V. This compact tester complies with the latest version of EN61243-3 2010 and is supplied with removable probe caps for GS38 compliance. It is ergonomically designed and of durable construction for both industrial and domestic applications. The 1.2m cable is double insulated with a black outer and contrasting inner core to give visual warning of damage to the cable.

- ◆ Auto detect AC/DC voltage
- ◆ Single pole phase test
- ◆ Phase rotation test
- ◆ Continuity test – LED and buzzer
- ◆ Auto power off
- ◆ White LED torch light

**Adds phase rotation and torch**

**Also available as VT25PD with a VT25 and a PD690 Proving Unit in a carry case (TC70)**

### ACCESSORIES

TC2A calibration  
 TC2B calibration (VT25PD)  
 CAPVT25 spare GS38 caps

CAT III  
1000V

CAT IV  
600V



## VT28

**Voltage range:** 12-690V AC/DC  
**Frequency range DC:** 16-400Hz  
**LED indication:** ±12, 24, 50, 120, 230, 400, 690V  
**LCD Display:**  
 Range: 10V-690V (DC, 16Hz-400Hz)  
 Resolution: 0.1V  
 Accuracy: ± (3% + 5 dgts)  
**Single pole phase test:**  
 100-690V AC RMS  
**Frequency range DC:** 50-60Hz  
**Phase rotation test:**  
 120-400V AC RMS  
**Frequency range DC:** 50-60Hz  
**Continuity range:** 0-500kΩ  
**GS 38 caps:** removable  
**Standard & regulations:**  
 BS EN 61243-3 2010  
**Cable length:** 1.2m  
**IP rating:** IP64  
 Auto power off  
**Torch light:** White LED  
**Power:** 2 x 1.5V AAA  
**Weight:** 130g (with batteries)  
**Dimensions:** 205 x 67 x 27mm  
**Includes:** battery and manual

## Two Pole Voltage Tester with LCD Display

The VT28 shares the same useful functions as the VT25 but has the additional benefit of an LCD display. All voltage, continuity and phase rotation indications have the same bright LED indication but the VT28 also displays the measured voltage reading on the 25mm x 15mm LCD display.

**Adds 4 digit LCD display**

**Also available as VT28PD with a VT28 and a PD690 in a carry case (TC70)**

**Meets  
Latest  
Standard**

### ACCESSORIES

TC2A calibration  
 TC2B calibration (VT28PD)  
 CAPVT25 spare GS38 caps

CAT III  
1000V

CAT IV  
600V

