

Clamp Meters

	AC Current	DC Current	AC Volts	DC Volts	Ohms	Frequency	Max Conductor Size	True RMS	Min / Max	Backlight	Other	Safety
ET4	200.0A 2.0% ± 10 (50-60Hz)	200.0A 2% ± 5	mV,V to 600V 1.2% ± 5	mV, V to 600V 1.2% ± 5	Ω, kΩ, MΩ 1% ± 5	Hz	15mm Ø	—	—	✓	Autorange, Continuity, Diode Test, Non contact voltage, Torch, Hold, Auto power off	CAT III 600V
ET5	200A-0A 2.0% ± 10 (50-60Hz)	200.0A 2% ± 5	mV,V to 600V 1.2% ± 5	mV, V to 600V 1.2% ± 5 0.5% ± 2	Ω, kΩ, MΩ 1% ± 5	Hz	15mm Ø	—	—	✓	As above plus Capacitance, Duty cycle, Temperature	CAT III 600V
CM69	6.0000mA/ 60.00mA 600.0mA 6.000A/ 60.00A 1% ± 3	—	60.00V 600.0V 1% ± 3	60.00V 600.0V 1% ± 2	Ω, kΩ, 1% ± 2	—	20mm Ø	✓	Peak	✓	Autorange, Low pass filter, 1µA resolution, Hold, Auto power off	CAT III 600V CAT IV300V
CM51	40.00A 300.0A 1.8% ± 5 (40-500Hz)	—	—	—	—	—	27mm Ø	—	—	—	Autorange, Hold, Auto power off	CAT III 300V
CM55	40.00A 400.0A 1.9% ± 3	—	400.0V 600V 1.2% ± 3	400.0V 600V 1% ± 3	400 Ω 1% ± 2	—	25mm Ø 35x15mm	—	—	—	Autorange, Hold, Auto power off	CAT III 600V
CM57	60.00A 600.0A 1.9% ± 5	—	mV,V to 600V 1.2% ± 5	mv, V to 600V 1% ± 3	Ω, kΩ, MΩ 1.2% ± 3	Hz, kHz	25mm Ø 35x15mm	✓	—	✓	Autorange, Non contact voltage, Smart measurement, Capacitance, Diode Test, Hold, Auto power off	CAT III 600V
CM79	60.00A 600.0A 1.9% ± 5	60.00A 600.0A 2% ± 5	600.0V 1.2% ± 5	600.0V 1% ± 5	1000.0Ω 1% ± 2	—	25mm Ø 45x15mm	✓	✓	✓	Autorange, Hold, Auto power off	CAT III 600V
CM95	4.000A 40.00A 400.0A 3.0% ± 5	—	—	—	—	—	85mm Ø	✓	✓	✓	1mA resolution, Flexible, Inhibit for logging, Hold, Auto power off	CAT IV 600V
CM100	30.00A 300.0A 3000A 3% ± 5	—	—	—	—	—	160mm Ø	✓	✓	✓	Flexible, Auto power off Inhibit for logging, Hold	CAT IV 600V
CM82	40.00A 400.0A 1000A 2% ± 6 (50-60Hz)	—	mV, V to 750V 1.5% ± 5	mV, V to 1000V 0.5% ± 2	Ω, kΩ, MΩ	Hz, kHz, MHz	51mm Ø 70x18mm	—	—	—	Diode Test, Capacitance, Auto/manual range, Hold, Auto power off	CAT IV 600V
CM84	400.0A 1000A 2% ± 6	400.0A 1000A 2% ± 5	mV, V to 750V 1.5% ± 5	mV, V to 1000V 0.5% ± 2	Ω, kΩ, MΩ	Hz, kHz, MHz	57mm Ø 70x18mm	—	—	—	Diode Test, Auto/manual range options, Hold, Auto power ofof	CAT IV 600V
CM87	660.0A 1500A 2% ± 10 (50-60Hz)	660.0A 2000A 2% ± 5 (<660A)	V to 750V 1.5% ± 8	V to 1000V 0.5% ± 2	Ω, kΩ, MΩ	Hz, kHz, MHz	57mm Ø 70x18mm	✓	✓	✓	Diode Test Capacitance, Inrush, Hold, Temperature, Auto power off,	CAT IV 600V
CMi210	600.0A 1500A 2.5% ± 10 (50-60Hz)	600.0A 2000A 2% ± 5 (<660A)	mV, V to 750V 1.5% ± 8	mV, V to 1000V 0.5% ± 2	Ω, kΩ, MΩ	Hz, kHz, MHz	57mm Ø 70x18mm	✓	✓	✓	50-1000V Insulation Test, Inrush, HFR filters, Capacitance, Diode Test, Temperature Duty cycle, Hold	CAT IV 600V