



MTLW3000

LEDs
UP TO
140W



MLB3000/MLW3000

LEDs
UP TO
140W



SLW2400

MTLW3000

3000W PIR Light Controller

- 12m detection range with 200° area of detection.
- Adjustable light level control.
- IP55 weatherproof rating.
- Adjustable light ON time 5 seconds to 18 minutes.
- Manual ON/OFF override.
- Hinged back box for ease of wiring.
- Total PIR switching: 3000W halogen/incandescent, 500W fluorescent/low energy plus 140W LED.

5 YEAR
GUARANTEE
INCLUDED

The MTLW3000, MLB3000 and MLW3000 carry a 5 year guarantee.

MLB3000

3000W PIR Light Controller – Black

- 12m detection range with 200° area of detection.
- Light ON times adjustable from 5 seconds to 18 minutes.
- Scrolling LED 'System Live' status acts as advance deterrent.
- Adjustable light level control.
- Manual ON/OFF override.
- Optional holiday mode between 1 and 8 hours.
- Direct mount bracketless fixing – contractor quick fit aid supplied.
- IP55 weatherproof rating.
- Total PIR switching: 3000W halogen/incandescent, 500W fluorescent/low energy plus 140W LED.

MLW3000

White Version

Shares all the features and benefits of the MLB3000 but is available in a white finish.

SLW2400

2000W PIR Light Controller

- 12m detection range with 180° area of detection.
- Adjustable light level control.
- IP44 weatherproof rating.
- Adjustable light ON time 5 seconds to 18 minutes.
- Manual ON/OFF override.
- Hinged back box for ease of wiring.
- Total PIR switching: 2000W incandescent/halogen, 500W fluorescent/low energy.

See page 91 for product specifications.



NSLDD1000

LEDs
UP TO
80W

NSLDD1000

3000W Dusk to Dawn Light Controller

- Hinged front cover for ease of wiring.
- Dusk light level adjustment.
- Light ON time is adjustable in 5 steps (2, 4, 6, 8 hours or until dawn).
- IP55 weatherproof rating.
- Switching delay avoids nuisance switching.
- Total light switching: 3000W incandescent/halogen, 500W fluorescent/low energy plus 80W LED.

All these products carry a 3 year guarantee.



MLSA360N – Surface Mount

LEDs
UP TO
140W

MLSA360N

360° PIR Light Controller

- Adjustable PIR detector with pan and tilt sensor aiming adjustment.
- Enhanced 360° detection zone for optimum coverage.
- Up to 12m detection range at 2.8m mounting height.
- Multiple mounting options – surface, ceiling and corner mounting.
- Immediate illumination of lights on exit and approach.
- Light ON time adjustment 5 seconds to 12 minutes.
- LUX (light level) adjustment – Day to Night (5 to 1000 LUX – permanently ON when at max.).
- Total PIR switching 3000W incandescent/halogen, 500W fluorescent, and 140W LED lighting.
- IP45 weatherproof rating.
- Optional mode settings – manual, Dusk to Dawn and Test mode.
- Corner mount bracket supplied in pack.
- Easy installation with Fast-fix terminal block connection.



SLB2300/SLW2300

LEDs
UP TO
140W

SLB2300

2300W PIR Light Controller – Black

- Powerful PIR controller for new and existing installations.
- Total PIR switching: 2300W incandescent/halogen, 500W fluorescent/low energy plus 140W LED.
- 12m detection range with 180° area of detection.
- Pan and tilt feature.
- Light ON times adjustable from 5 seconds to 15 minutes.
- LUX (light level) adjustment – Day to Night (2 to 1000).
- Manual ON/OFF switching override.
- IP55 weatherproof rating.
- Simple and quick to fit terminal block connectors.
- Dimensions: 93 x 78 x 141mm.
- Corner mounting bracket available – SLBCB.

SLW2300

White Version

- Corner mounting bracket available – SLWCB.



TOP TIP

Increase the detection area of the MLSA360N with the corner bracket. When fitted this enables the unit to 'see' around a chosen corner and along both walls so you can be more secure using one detector.



MLSA360N Ceiling Mount

SLBCB

Corner Bracket for PIR Light Controller SLB2300

- Simply screw fit to wall with controller's wall plate and click fit controller into position.
- Ideal for narrow passageways and corner entrance/exit points.

SLWCB

Corner Bracket for PIR Light Controller SLW2300

Shares all the features and benefits of the SLBCB but is available in a white finish.

