Rittal – The System.

Faster – better – everywhere.

Baying enclosure system VX25 Basic enclosure – VX 8405.000

Date : Jul 23, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Baying enclosure system VX25 Basic enclosure – VX 8405.000

created: 23.07.2018 on www.rittal.com/com-en

Product description

Material:	Enclosure frame: Sheet steel, 1.5 mm Roof: Sheet steel, 1.5 mm Door: Sheet steel, 2.0 mm Rear panel: Sheet steel, 1.5 mm Gland plates: Sheet steel, 1.5 mm Mounting plate: Sheet steel 3.0 mm
Surface finish:	Enclosure frame: Dipcoat-primed Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	NEMA 12
IK Code:	IK10
Supply includes:	Enclosure frame Door(s) Door hinged on the right, may be swapped to the left Roof plate Rear panel Gland plates Mounting plate 2 punched rails 18 x 39 mm Lock: 3 mm double-bit
Basic material:	Sheet steel

© Rittal 2018

Product features

Dimensions:	Width: 400 mm Height: 2000 mm Depth: 500 mm
Mounting plate:	Width: 299 mm Height: 1896 mm
Number of doors:	1
Packs of:	1 pc(s).
Weight/pack:	60.7 kg
EAN:	4028177919280
Customs tariff number:	94032080
ETIM 6.0:	EC000261
ETIM 5.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 7.0/7.1:	27180101
eCl@ss 6.0/6.1:	27180101
eCl@ss 5.1/5.1.4:	27180101
Product description (long):	VX Baying enclosure system, WHD: 400x2000x500 mm, sheet steel, with mounting plate, single door at the front

Approvals

Approvals:	CSA Lloyds Register of Shipping UL + C-UL
Certificates:	IK-Code
Declarations:	Declaration of conformity

© Rittal 2018