




12W LED BULKHEADS

Robustly constructed, reliable wall fitting offering more discrete illumination for utility applications.

- Tough polycarbonate housing • Hinged diffuser
- Opal diffuser: evenly diffused light output
- Corrosion resistant stainless steel cover fixing screws
- Cable channel on reverse of fitting with 20mm knockout conduit entries

BULKLEDPC
• Integral photocell: automatic dusk to dawn operation



Code	Version	Colour	Wattage	Colour Temp.	Luminaire Lumens	Avg. Rated Life (Hrs)	IP Rating	MOM / OPQ
BULKLED	Standard	Black	12W	6500K	1250 lm	30,000 hrs	IP65	1 / 12
BULKLEDPC	Photocell							



LED LAMP SPECIFICATIONS:	
Luminaire lumens (with diffuser)	1250 lm
Lumens from chip (no diffuser)	1650 lm
Useful lumens	705 lm
Rated Wattage	12W
Rated luminous flux	705 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	6500K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60% of the full light output	Instant full light
Dimmable	No
Nominal beam angle	120°
Rated power	12W
Rated lamp lifetime	30,000 hrs
Displacement factor	≥0.7
Lumen maintenance factor at end of nominal life	≥0.8
Starting time	Instant full light
Colour rendering	≥80
Colour consistency	Within a six step Macadam ellipse
Rated peak intensity	294cd
Rated beam angle	120°
Voltage / Frequency	240V~50Hz
Lumen efficacy: 104 lm / W	
This product contains a Light Source of Energy Efficiency Class D	
Class 2 double insulated	
Not suitable for accent lighting	



5
Year Warranty

