



Indus

5ft Single non-corrosive linear luminaire for Kosnic LED T8 lamps with built-in emergency

The Kosnic Indus IP65 Battens for T8 LED Tubes are designed specifically for use with Kosnic's T8 LED Tubes. The luminaires are suitable for a wide range of indoor and outdoor commercial applications including warehouses, factories and garages, and have the option to include built-in emergency modules. The Kosnic T8 LED Tubes themselves utilise high performance LEDs to offer outstanding lumen efficiency with a long operational life helping to reduce building energy and maintenance costs.

KBTNT8LS655F1/E

Specification

| | |
|----------------------------------|---------------------|
| Voltage (eg 220-240 Vac 50/60Hz) | 220-240Vac 50/60Hz |
| Rated Power (W) | 50 |
| Dimensions L x W x D (mm) | 1565 x 86 x 90 |
| Protection Rating | Class I |
| IK Rating | IK08 |
| IP Rating | IP65 |
| Ambient Temperature Range (°C) | -20 to 40 |
| Emergency Luminous Flux (lm) | 300 with CEW05LBL/N |

Light Source Specification

| | |
|--|-----------|
| Light Source Cap Type (or other interface) | Terminals |
|--|-----------|

Gears and Accessories

| | |
|-------------|--|
| Component 1 | for 1 x 5ft LED T8 Lamp |
| Component 2 | Lamp Holder G 13 |
| Component 3 | LOR (%) 92 |
| Component 4 | Mounting Spacing LF (mm) 1000 |
| Component 5 | Emergency Module CEW05LBL/N |
| Component 6 | Battery Pack for Panel EME Module KBAT2600 |

Technical Drawings

