




Suitable for use with all electrical appliances, in public washrooms and areas where water is present, plus fixed electric appliances such as domestic machines in the home, cold drink dispensers and hotel hairdryers.

- Mechanically latched (does not need resetting after a power loss)
- High intensity LED power on indicator, clear visual indicator of power on
- Mechanical flag trip indicator
- Integral cord outlet and cable clamp
- Fuse holder can be locked out for safety
- Twin earth terminals

Technical Data

Rated voltage	230V AC 50Hz
Max operating current	13A (13A inductive)
Rated trip current	30mA
Typical trip speed	Less than 20ms (typical)
RCD contact break	Double pole
Latching	Mechanical, no need to reset after power loss (passive)
Responsive to	Pulsating DC earth faults
Conforms to	BS 1363-4:1995 Amd 1, 2, 3 and BS 7288:1990 Amd 1
EMC Emissions	EN 55014-1:2006 & EN 55014-1:2000 inc A1:2001 & A2:2002
EMC Immunity	EN 61543:1995 inc A11:2003, A12:2005 & A2:2006

PART NO.	DESCRIPTION	Colour	
H92WPA-C	RCD Spur Scratch resistant urea front plate Fits 25mm standard back box	White	
H92MPA-C	RCD Spur Complete with metal back box (IP66 option available PXC92MP-C on page 22)	Metalclad	



H92WPA-C



H92MPA-C