
CONTROLS

Technical Specification









General Information

Dimensions	80mm (W) x 51.5mm (H) x 119.5mm (D)	
Materials	Body: Polycarbonate (UV Stabilised)	
Finish	Black	
Typical Mounting	Vertical / Wall	
Working Humidity	<93%RH	
Ingress Protection	IP65	
Warranty	5 Years	


Supply & Power


Input Voltage & Frequency	220-240V~ 50/60Hz	
Terminations	Input: Permanent Live & Neutral	
	Output: Switched Live (All Screw Terminals)	
Electrical Safety	Class II (Double Insulated)	
Load Rating	300W - LED & Compact Fluoresent	
	1200W - Incandescent & Halogen	
Zero Cross Technology	Yes	
Power Consumption	0.5W Approx.	
Ambient Temperature (Ta)	-20°C - +40°C	

Sensor Parameters & Settings

	<u> </u>	
Installation Height	1.8 Metres to 2.5 Metres	
Detection Distance	12 Metres Max. (<24°C)	
Detection Angle	180°	
Detection Motion Speed	0.6-1.5m/s	
Manual Adjustments	Time Delay	10 Seconds (Min. +-3 Seconds) to 15 Minutes (Max. +- 2 Minutes)
	Lux Level	3 Lux (Minimum) to 2000 Lux (Maximum)

Detection Area Schematics









T: +44 (0)1827 300640

E: sales@oviaUK.com | W: oviaUK.com