



Description: 30W 600mm x 600mm LED Panel - 3000K - White






Scolmore

General Information

General Information		Supply & Power	
Dimensions	595mm x 595mm x 9mm	Input Voltage & Frequency	220-240V~ 50/60Hz
Materials	Frame: Powdercoated Aluminium	Electrical Safety	Class II (Double Insulated)
	Diffuser: Polypropylene	Input Power	30W
	Light Guide Plate (LGP): Polystyrene	Input Current	134mA
Finish	White (RAL 9003)	In-rush Current	8.06A (230µs)
Product Weight	2.2Kg	Power Factor	>0.9
Dimmable	No	Ambient Temperature (Ta)	-20°C - +40°C
Ingress Protection	IP20	Critical Temperature	+75°C
Flammability Rating	TP(a)	LED Driver	Remote Driver Supplied
Warranty	3 Years	Termination	In To Driver (Screw Terminals)

Accessories

OVEMCG50	3 Hour Emergency Pack	Colour Temperature	3000K
OVSURF731	600mm x 600mm Surface Frame Kit	CRI	>80
OVREC731	600mm x 600mm Recess Frame Kit	Typical Luminous Flux	2850lm
OVSUSP731	Suspension Wire Kit	Efficacy	95lm/W



Luminaire Output

Lammano output			
Colour Temperature	3000K		
CRI	>80		
Typical Luminous Flux	2850lm		
Efficacy	95lm/W		
Beam Angle	120°		
LED Lifetime (L70)	30,000 Hours		

3 (PA)

Page 1 Errors & Omissions excluc Specification is subject to change without not

(IP20)

Additional Information

Suspension hooks pre-fitted to the back

OVIA Limited, 1 Scolmore Park, Landsberg, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7XB United Kingdom **T:** +44 (0)1827 300640 E: sales@oviaUK.com | W: oviaUK.com