

EXTERNAL ELECTRO-MAGNETIC LOCKS

DEEDLOCK EXTERNAL ELECTRO-MAGNETIC LOCKS

AEMGATE/F/S	External Magnet Side & Face Fix Monitored - Min. holding force 1100 lbs (4890N)
AEMBR046	Z Bracket for AEMGATE/F/S
AEM/MINGATE/F/S	External Mini-gate Side & Face Fix Magnet - Monitored - Min. holding force 500LBS (2220N)
AEMBR056	Z Bracket for AEM/MINGATE/F/S

DEEDLOCK CUPBOARD/CABINET & MICRO ELECTRO-MAGNETIC LOCKS

DEEDLOCK CUPBOARD/CABINET & MICRO MAGNETIC LOCKS

AEM200	Deedlock Cupboard/Cabinet Magnetic lock c/w L bracket (80lbs Holding force)
AEMBR200	Deedlock Z Bracket to suit AEM200 Magnet
AEM-ML300	Micro Mortice Magnet Unmonitored suitable for cupboards and lockers - 12/24V DC
AEM-ML300H	Micro Surface Magnet Unmonitored suitable for cupboards and lockers - 12/24V DC
AEM-MLBR01	Z & L Bracket Set for AEM-ML300H to suit Inward opening door
AEM-MLBRL	Adjustable Transom L Bracket for AEM-ML300H to suit outward opening door

SPECIAL APPLICATION LOCKING PRODUCTS

- The ADA66 & ASA66 have a holding force of 10,000N
- Corrects misalignment of up to +8mm
- Instant release with 100kg of side load pressure
- AGL66 lock has 50,000N holding force
- IP66 ingress protection
- Built-in heater when powered by 24V DC



SPECIAL APPLICATION LOCKING PRODUCTS

ASA66	Single Action, Motor Driven Electronic Lock 12/24V DC (10,000N Holding Force)
ASA66/H	Surface Housing & Dress Plate to suit ASA66
ADA66	Double Action, Motor Driven Electronic Lock 12/24V DC (10,000N Holding Force)
ADA66/H	Surface Housing & Dress Plate to suit ADA66
NEW AGL66	Gate & Roller Door High Security Lock (50,000N Holding Force)