

Cat ref.

Incomer Kits for 125A Boards

Description	Max Cable Capacity Solid	Cat ref.
3 Pole 100A Switch Disconnector Incomer Kit (Fits within distribution board)	50mm ²	JK11003S 4
4 Pole 100A Switch Disconnector Incomer Kit (Fits within distribution board)	50mm ²	JK11004S 4
3 Pole 125A Switch Disconnector Incomer Kit (Fits within distribution board)	50mm ²	JK11253S 4
4 Pole 125A Switch Disconnector Incomer Kit (Fits within distribution board)	50mm ²	JK11254S 4
4 Pole 63A Contactor Incomer Kit includes Switch Disconnector (fits below distribution board, 300mm high)	50mm ²	JK10634C ³
4 Pole 100A Contactor Incomer Kit includes Switch Disconnector (fits below distribution board, 450mm high)	M8 Lug	JK11004C ³
125A Direct Connection Kit (Fits within distribution board)	50mm ²	JK11254D
4 Pole 63A 30mA RCCB Type A Incomer Kit (Fits within distribution board)	25mm ²	JK10634RH
4 Pole 100A 30mA RCCB Type A Incomer Kit (Fits within distribution board)	50mm ²	JK11004RH
4 Pole 100A 300mA RCCB Type A Incomer Kit (Fits within distribution board)	50mm ²	JK11004RL
4 Pole 100A 300mA Time Delayed RCCB Type A Incomer Kit (Fits within distribution board)	50mm ²	JK11004RLD
4 Pole 100A 100mA RCCB Type A Incomer Kit (Fits within distribution board)	50mm ²	JK11004RM
4 Pole 100A 100mA Time Delayed RCCB Type A Incomer Kit (Fits within distribution board)	50mm ²	JK11004RMD
125A 4 pole Changeover Incomer Kit (Fits within distribution board)	50mm ²	JK11254CO ³

Side by Side Incomer Kits for 125A Boards

Characteristics:

- Complete with 125A 3P SD incomer

- Cable sets to connect to distribution boards
- Suitable for all 125A TP&N board sizes

Description	Cat ref.	
Dual kWh Meter Pack 125A Incomer Pulsed & Modbus	M8 Lug	JKD125MID *
Triple kWh Meter Pack 125A Incomer Pulsed & Modbus	M8 Lug	JKD125TMID ★

Surge Protection Kits for 125A Boards

Characteristics:

- SPD kit for direct integration within 125A TPN boards

Low U_p value assured through use of solid busbar connectors and solid copper Earth
SPD suitable for TN / TT Earth arrangements including TNC-S (PME)
CT2 type SPD to accommodate multiple Earthing systems.
Coordination verified with upstream Hager Panelboard SPDs.

Description

Type 1 & 2 Surge Protection Kit for 125A TP&N Boards	JK101SPD ★
Type 2 Surge Protection Kit for 125A TP&N Boards	JK102SPD ★
Type 1 & 2 Surge Protection Kit for 125A Dual Metered Boards	JKD101SPD ★
Type 2 Surge Protection Kit for 125A Dual Metered Boards	JKD102SPD ★

Meter Packs & Kits for 125A Boards - MID

Characteristics:

- JKD1125MID – This enclosed meter pack fits below any Hager standard 125A TPN boards. Can be used in conjunction with SPD kits – MID meter has Modbus and pulse comms.

- JK140MID – This MID meter kits can be fitted within the TPN board, but is not suitable for 4 & 6 way boards. This kit can
not be used, when an SPD is fitted – MID Meter has Modbus and pulse comms.

Description	Cat ref.
Meter Enclosure & MID Meter	JKD1125MID *
Multifunction Meter Pack 125A Pulsed & Modbus	JK140MID *

16A	20A	25A	32A	40A	45A	50A	63A
NBN116A	NBN120A	NBN125A	NBN132A	NBN140A	-	NBN150A	NBN163A
NBN316A	NBN320A	NBN325A	NBN332A	NBN340A	-	NBN350A	NBN363A
NCN116A	NCN120A	NCN125A	NCN132A	NCN140A	-	NCN150A	NCN163A
NCN316A	NCN320A	NCN325A	NCN332A	NCN340A	-	NCN350A	NCN363A
NDN116A	NDN120A	NDN125A	NDN132A	NDN140A	-	NDN150A	NDN163A
NDN316A	NDN320A	NDN325A	NDN332A	NDN340A	-	NDN350A	NDN363A
ADA116U *	ADA120U *	ADA125U *	ADA132U *	ADA140U *	ADA145U *	-	-
ADA166U *	ADA170U *	ADA175U *	ADA182U *	ADA190U *	-	-	-



JK11003S ³ A 300 / 450mm space is required below the board for fitting.

⁴ For single phase supply applications, JK1SPKIT can be used with these incomer options.



JKD125MID



JK101SPD

