



Available In White, Chrome (CH), Brass (BR) Or Black (BK).
Simply Insert Colour Suffix into Code

- 5500K Colour Temperature
- Viewing distance - 25m
- SMT 5050 LED Lamp
- Steel housing
- Wall mounted
- Charge and discharge protection
- Green LED Indicator
- 3 Hours Emergency Duration
- 3.6V 1800mAH NI-CAD Battery
- BS EN 60598-2-22 Standards
- Dimensions - 390 x 190 x 60mm
- Weight - 1.3Kg

EMLED3WMEXBOX

3W LED Maintained Emergency Sign



EMBAT3.6V1800
3.6V 1800mAH Battery



EMLED3WMEXBOXU**
3W LED Maintained
Emergency Sign UP



EMLED3WMEXBOXD**
3W LED Maintained
Emergency Sign DOWN



EMLED3WMEXBOXL**
3W LED Maintained
Emergency Sign LEFT



EMLED3WMEXBOXR**
3W LED Maintained
Emergency Sign RIGHT



- 5500K Colour Temperature
- Viewing distance - 24m
- SMD 3528 Lamp
- Polycarbonate frame with legend
- Ceiling or wall mounted
- Charge and discharge protection
- Green LED Indicator
- 3 Hours Emergency Duration
- 4.8V 600mAH Battery
- BS EN 60598-2-22 Standards
- Dimensions - 305 x 160 x 225mm
- Weight - 0.8Kg

EM2WMEXSIGN

LED 2W Maintained Exit Sign Legend



EMBAT4.8V600
4.8V 600mAH Battery



EMWMBEXHSIGN
Hanging Sign Wall Bracket



EM2WMEXSIGNU
LED 2W Maintained
Exit Sign Legend UP



EM2WMEXSIGND
LED 2W Maintained
Exit Sign Legend DOWN



EM2WMEXSIGNL
LED 2W Maintained
Exit Sign Legend LEFT



EM2WMEXSIGNR
LED 2W Maintained
Exit Sign Legend RIGHT