

SBC - Solid Board Cutters & Accessories

Perfect for.....

Drill easy fix access holes in solid boards in under a minute

arme CUTTER

COBALT

Available in 111mm & 127mm sizes



111mm

127mm

A Depth Stop Ring

Precision manufactured depth-stop ring set to the same depth as the cap rebate makes it impossible to over-drill meaning the cap lies flush to the floor for a neat finish with 100% accuracy

B Rebating Cutters

Hardened steel rebating cutters produce a 6.5mm(1/4") rebate in the floor material creating a ledge for the SBC caps to precisely locate on in the flooring

Cobalt Cutting Teeth C

Tougher tooth design manufactured with M42 superior steel featuring 8% Cobalt provides excellent wear resistance properties at higher drilling temperatures. This gives extended tool life, and lasts at least 100% longer than standard bi-metallic holesaws

SBC can be used in:

• Flooring grade chip board up to 22mm thick

SBC is ideal when creating holes for:

- · Running cables under floors for rewires / installations Access above downlighters during
- installation or maintenance • Access when running pipework
- under flooring General work where DID
- access to the floor void under solid flooring is required

SBC caps are removable allowing for repeat access into solid floors

YOU

KNOW?




- Solid Board Cutters & Accessories SRC

Description	Contents	Part Number
111mm Complete Set	1x111mm Cobalt Solid Board Cutter 3x111mm Plugs 1xHexagon Drive Adaptor for SBC Cutter 1xSDS Plus Drive Adaptor for SBC Cutter	SBC111SET
111mm Plug Set	1x111mm Cobalt Solid Board Cutter 3x111mm Plugs	SBC PLUGSET
111mm Plug x 1		RPSBC111PLUG
111mm Plugs - pack of 10		SBC111PLUGX10
127mm Complete Set	1x127mm Cobalt Solid Board Cutter 3x127mm Plugs 1xHexagon Drive Adaptor for SBC Cutter 1xSDS Plus Drive Adaptor for SBC Cutter	SBC127SET
127mm Plug Set	1x127mm Cobalt Solid Board Cutter 3x127mm Plugs	SBC127PLUGSET
127mm Plug x 1		RPSBC127PLUG
127mm Plugs - pack of 10		SBC127PLUGX10

Operation Speed Chart

Diameter Size mm	Recommended RPM	
111mm	900	
127mm	900	





TIP! When using in waterproof boards, if it is required to maintain the waterproof integrity of the board, it is advisable to seal around the edges of the rebated cap with silicone sealant or similar

TECH





with relevant with relevant adaptor adaptor

Ideal machines will have: 850w Slipping Clutch



SBC can be used with standard holesaw adaptors with a 5/8" - 18 UNF thread. Try the Hex Shank (part no. CHD32-64HEX) or the SDS Plus Shank (part no. CHD32-64SDS). See page 80.

