

LFHP system

galvanised steel extra LFH coated, pliable



TRANSPORT
FOR LONDON
EVERY JOURNEY MATTERS



P - plain hole connector nickel plated brass

Two part fitting comprising shell and body without thread. The body is fitted through the opposite side of the entry to the conduit and acts as a locking device also providing a smooth entry bush.

IP40



90° elbow - internal and external threaded nickel plated brass elbow

90° elbow which can be screwed onto external threaded fittings.



LFHP

Construction: Corrugated galvanised steel with kraft paper lining and smooth extra LFH outer cover.

Colour: Black.

Typical Applications: Any installation where there is no movement and a high IP rating is required.

APR Cert No.297



external thread nickel plated brass

Multipart compression fitting including serrated elastomeric seal. Can be used for knockout or threaded entries as fitting rotates until tightened.

IP66

IP67



hole size (mm)	part number
16	FB16-P
20	FB20-P
25	FB25-P
32	FB32-P

metric thread part number
BM90-16M
BM90-20M
BM90-20M
BM90-25M
BM90-32M

LFHP	part number	reel length (m)	min inside bend radius (mm)	outside dia (mm)	inside dia (mm)
	LFHP20B	25	40	20.9	14.6
	LFHP25B	25	55	27.3	20.4
	LFHP32B	25	65	34.0	26.7

metric thread part number
FLP20-M20-C
FLP25-M25-C
FLP32-M32-C

nominal size (mm)
16
16
20
25
32