# Hamilton Technical Specification

## DIGITAL TELEVISION SOCKETS - Screened Non-Isolated, DAB compatible

#### **CATEGORY:**

#### **DIGITAL TV COAXIAL SOCKETS**

#### Technical Insert Ref: Description:

**DENT** Non-Isolated TV/FM/Satellite 1/Satellite 2

Quadplex 2 In/ 4 Out

DSAT+ Non-Isolated TV/FM/Satellite 1/Satellite 2

Quadplex 2 In/ 4 Out + TVF + TCS

**DTRID** Non-Isolated TV/FM/Satellite

Triplexer 1 In/3 Out

1 gang Non-Isolated Satellite **DSAT** DTVF 1 gang Non-Isolated TV (female)

DTVM 1 gang Non-Isolated TV (male)

#### **EUROFIX MODULES**

#### Technical Insert Ref: Description:

MOD-DENT Non-Isolated TV/FM/Satellite 1/Satellite 2

Quadplex 2 In/ 4 Out

MOD-DSAT 1 gang Non-Isolated Satellite Non-Isolated TV/FM/Satellite **MOD-DTRID** 

Triplexer 1 In/3 Out

MOD-DTVF 1 gang Non-Isolated TV (female) 1 gang Non-Isolated TV (male) MOD-DTVM

#### **TECHNICAL SPECIFICATION:**

IP2XD IP Rating:

**Product Class 1:** Must be earthed (ref BS7671 415.2.1)

-5 to +40 C

**Ambient Operating Temperature:** 

Location: Internal Use Only 2000m

Max Installation Altitude:

Standard Hamilton manufactured electrical accessories are designed to be mounted on BS4662:2006 flush wall boxes.

Note: Mains operated and extra low voltage products must not be installed in the same face plate aperture. When installing within the same back box a suitable barrier MUST be used to separate the two voltages. See BS 7671 Wiring regulations for further details.

#### **TERMINAL CAPACITY:**

	1mm²	1.5mm <sup>2</sup>	2.5mm <sup>2</sup>	4mm² Multi-Strand	6mm²
Earth Terminal Capacity	5	4	3	1	1

### **FREQUENCIES:**

DTVM	Frequency 1	FM DC	5-2200 MHz	
DSAT	Frequency 1	SAT DC	5-2200 MHz	
DTVF	Frequency 1	TV DC	5-2200 MHz	
DENT/DTRID/DSAT+	Frequency 1	TV	5-68 MHz 125-860 MHz	
	Frequency 2	FM	88-108 MHz	
	Frequency 3	SAT DC	950-2200 MHz	
DSAT+	Frequency 4	TV DC	5-2200 MHz	

#### **DIGITAL TELEVISION SOCKETS EUROFIX DIGITAL TV SOCKET MODULES** Fixing Centres: Fits one Euro1 0 Ö...Ö Õ aperture MOD-DSAT DENT MOD-DTVF DTRID 60.3mm MOD-DTVM 0 0 0 Fits one Euro2 0.0 aperture Õ DTVF DSAT MOD-DENT MOD-DTRID 120.6mm DSAT+