
Hamilton

www.hamilton-litestat.com



Insert Type Plate Finish White Frame Finish White Switch Colour Body & Switch Trim Double = 86mm Double = 146mm Height Width Depth **Fixing Hole Centres** Minimum Wall Box Depth 35 Wattage Switched Poles **Current Rating** Voltage Max load Contact Gap Minimum Terminal Capacity 1 Terminal Capacity 2 **Terminal Capacity 3** Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5

BS EN 60669-2-1

Push On/Off 3 Gang 2 Way 300 max 40 min

Plastic Dimmer

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Correct as at August 2012 E&OE

Product Class 1 Ambient Operating Temperature Recommended Location Standard/Approval

Patents and Trademarks

Primary Range

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary) Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire Registered in London No. 941624 • VAT Registration No. 222 6607 84



