


Item Image



Wiring



I RRT SS-W

Grid Fix Insert Rocker PTM/BRK 10AX Satin Steel/White. Standard Insert will be Satin Steel with a White surround.

| | |
|-------------------------------|---|
| Primary Range | GRID-IT |
| Insert Type | Retractive Push to Make Rocker Switches |
| Plate Finish | |
| Frame Finish | |
| Switch Colour | Satin Steel |
| Body & Switch Trim | White |
| Height | |
| Width | |
| Depth | |
| Fixing Hole Centres | |
| Minimum Wall Box Depth | 35mm |
| Wattage | |
| Switched Poles | Single |
| Current Rating | 10AX |
| Voltage | 220/250V AC |
| Max load | 10 Amp inductive |
| Contact Gap Minimum | 3mm |
| Terminal Capacity 1 | 5 x 1mm ² |
| Terminal Capacity 2 | 4 x 1.5mm ² |
| Terminal Capacity 3 | 2 x 2.5mm ² |
| Terminal Capacity 4 | 2 x 4mm ² Multi-Strand |
| Terminal Capacity 5 | 1 x 6mm ² |
| Earth Terminal Capacity 1 | 6 x 1mm ² |
| Earth Terminal Capacity 2 | 5 x 1.5mm ² |
| Earth Terminal Capacity 3 | 3 x 2.5mm ² |
| Earth Terminal Capacity 4 | 2 x 4mm ² Multi-Strand |
| Earth Terminal Capacity 5 | 1 x 6mm ² |
| Product Class 1 | Face plate must be earthed |
| Ambient Operating Temperature | -5° to +40° C |
| Recommended Location | Indoor use only |
| Standard/Approval | BS EN 60669-1 |
| Patents and Trademarks | |

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.

Correct as at August 2012
E&OE

R Hamilton & Co Ltd • Quarry Industrial Estate • Mere • Wiltshire • BA12 6LA • UK
T: +44 (0)1747 860088 • F: +44 (0)1747 861032 • E: info@hamilton-litestat.com
www.hamilton-litestat.com

Directors: R Hamilton • I Hamilton • RL Haines • CP Savory • AMH Hamilton (Secretary)
Registered Office: Cedar House • Breckland • Linford Wood • Milton Keynes • MK14 6EX • Buckinghamshire
Registered in London No. 941624 • VAT Registration No. 222 6607 84



BS EN ISO 9001:2008
CERT. No. FM11238

