



Rating	Module width (35mm)	Part Number
Three pole		
Breaking capacity 36kA at 415V 3 phase		
16	3	MGP0163X
25	3	MGP0253X
32	3	MGP0323X
40	3	MGP0403X
50	3	MGP0503X
63	3	MGP0633X
80	3	MGP0803X
100	3	MGP1003X
125	3	MGP1253X
160	3	MGP1603X
200	3	MGP2003X
250	3	MGP2503X
400	4 ⁽¹⁾ (2)	MGP4003X
630	4 ⁽¹⁾ (2)	MGP6303X

Four pole		
Breaking capacity 36kA at 415V 3 phase + neutral		
16	4	MGP0164X
25	4	MGP0254X
32	4	MGP0324X
40	4	MGP0404X
50	4	MGP0504X
63	4	MGP0634X
80	4	MGP0804X
100	4	MGP1004X
125	4	MGP1254X
160	4	MGP1604X
200	4	MGP2004X
250	4	MGP2504X
400	6 ⁽¹⁾ (2)	MGP4004X One MGPBB25 also required
630	6 ⁽¹⁾ (2)	MGP6304X One MGPBB25 also required

Disconnectable neutral links		
250	1	MGP250NL
630	2	MGP630NL One MGPBB25 also required

(1) If fitted in 630 or 800A board a shrouding kit is required.

(2) Breaking capacity 50kA at 415V.