

**Component
Selector
Chart**

PROFILE LENGTHS

Main
Carrier

Straight
Cover

Curved
Cover

Square
Cover

FITTINGS

Flexible
Internal
Corner

3 METRES

6m

3 METRES

30m

3 METRES

30m

3 METRES

30m

2



VP180WHI
VP180CHA

VP100WHI
VP100CHA*

VP110WHI x2
VP110CHA x2

VP181WHI
VP181CHA



VP180WHI
VP180CHA

VP100WHI
VP100CHA*

VP110WHI
VP110CHA

VP115WHI
VP115CHA

VP191WHI
VP191CHA

* Use Charcoal lid to help achieve compliance to Part M

technical hotline +44 (0)1268 563720

perimeter and distribution | cable management

Flexible External Corner

CONSISTS OF COVER AND DATA SWEEP

2

End Cap

SUPPLIED AS LEFT AND RIGHT-HAND PAIR

1

Joint Cover

5

Flat Angle

CONSISTS OF COVER AND CARRIER

1

Flat Tee

CONSISTS OF COVER AND CARRIER

1

Adaptor

SUITABLE FOR 20 AND 25MM CONDUIT AND YT2 AND YT4 MINI-TRUNKING

10



VP182WHI
VP182CHA

VP183WHI
VP183CHA

VP184WHI
VP184CHA

VP185WHI
VP185CHA

VP187WHI
VP187CHA

VP188WHI
VP188CHA

VP192WHI
VP192CHA

VP193WHI
VP193CHA

VP194WHI
VP194CHA

Flat Angle Up
VP195WHI
VP195CHA

Flat Angle Down
VP196WHI**
VP196CHA**

VP197WHI
VP197CHA

VP198WHI
VP198CHA