

Technical Specification



Product Code: DPCH504WH Description: 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket

Dutlet





Representative Image

General Information

Dimensions 146mm (W) x 88mm (H) x 8mm (D)

Dimensions With Gasket 149mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Rounded Profile Polished Chrome

Insert & Gasket Colour White

Materials Front Plate: Stainless Steel

Insert & Rear Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 45A

Plate Fixing Centres 120.6mm (Vertical Fixing)

 Terminal Size
 6mmø

 Terminal Torque
 2.5Nm

 Terminal Capacity
 1 x 16mm²

 Double Pole
 Yes

 Twin Earth Terminals
 Yes

Ingress Protection IP20

Back Box Depth 35mm Minimum
Operational Temperature -5°C to +40°C
Warranty 10 Years

Standards BS 4177:1992

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.