


Product Code: PRW039

Description: 2A Round Pin Socket Outlet



## General Information

Dimensions	86mm (W) x 86mm (H) x 11mm (D)
Plate Design & Finish	Square Edge Polar White
Materials	Front Plate: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	2A
Plate Fixing Centres	60.3mm
Terminal Size	5mmø
Terminal Torque	0.5Nm
Terminal Capacity	3 x 1.5mm <sup>2</sup>
Switched	No
Twin Earth Terminals	No
Ingress Protection	IP20
Back Box Depth	25mm Minimum
Termination Type	Screw
Operational Temperature	-5°C to +40°C
Warranty	20 Years

**Standards** BS 546: 1950

## Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.