

Product Code: PRW017

Description: 20A Flex Outlet Plate



Representative Image

General Information

Dimensions	86mm (W) x 86mm (H) x 11mm (D)
Plate Design & Finish	Square Edge Polar White
Materials	Front Plate: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated
Maximum Voltage	250V~ 50Hz
Load Rating	20A
Plate Fixing Centres	60.3mm
Terminal Size	5mmø
Terminal Torque	1.8Nm
Terminal Capacity	3 x 2.5mm ² or 2 x 4mm ²
Twin Earth Terminals	Yes
Flex Outlet	Yes (Through Front & Bottom of the Plate)
Ingress Protection	IP20
Back Box Depth	16mm Minimum
Operational Temperature	-5°C to +40°C
Warranty	20 Years
Standards	BS 5733: 2010

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.
All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.