

Technical Specification



Product Code: CMA622

Description: 20A Double Pole Plate Switch



General Information Dimensions 86mm (W) x 86mm (H) x 9.5mm (D) Material Composition Front Plate & Rocker Switch: Urea Rear Housing: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel Maximum Voltage 250V~ 50Hz **Fixing Centres** 60.3mm **Terminal Size** 5mmø **Terminal Torque** 1.8Nm **Terminal Capacity** 4 x 2.5mm² **Double Pole** Yes Twin Earth Terminals Yes **Back Box Depth** 25mm Minimum **Temperature Rating** -5°C to +40°C Warranty 20 Years Standards BS EN 60669-1:1999 +A1:2002 +A2:2008 Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.