

Technical Specification



Product Code: DPBN571UBK Description: 13A Ingot 1 Gang Switched Socket Outlet With Single 2.1A USB Outlet





General Information

Dimensions With Gasket 91mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Black Nickel

Insert & Gasket Colour Black

Materials Front Plate: Stainless Steel, Insert: Urea

Housing: Nylon, Switch Cover: Stainless Steel

Terminals: Brass, Terminal Screws: Steel & Yellow Passivated

Contacts: Silver "on-lay" Copper / Brass, Internal Busbars: Formed Pressed Brass

PCB: Mixed Components, Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 13A
Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 1.2Nm

Terminal Capacity 4 x 2.5mm² or 2 x 4mm²

Single Pole Yes
Twin Earth Terminals Yes

USB Charging Output Total 5V DC, 2.1A

Number Of USB Outputs 1

USB Type USB Type "A"

USB Standby Current 2mA

Product Markings USB 5V 2.1A

Ingress Protection IP20

Back Box Depth 25mm Minimum

Termination Type Screw

Operational Temperature -5°C to +40°C

Warranty 10 Years, 1 Year Electronics

Standards BS 1363-2: 2016 +A1: 2018

BS EN 62368-1: 2014, BS EN 62680-1-1: 2015

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.