

Product Code: DPCH038BK

Description: 5A Round Pin Socket Outlet



### General Information

Dimensions	88mm (W) x 88mm (H) x 8mm (D)
Dimensions With Gasket	91mm (W) x 91mm (H) x 9mm (D)
Plate Design & Finish	Rounded Profile Polished Chrome
Insert & Gasket Colour	Black
Materials	Front Plate: Stainless Steel Insert: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	5A
Plate Fixing Centres	60.3mm
Terminal Size	5mmø
Terminal Torque	1.2Nm
Terminal Capacity	4 x 1.5mm <sup>2</sup> or 3 x 2.5mm <sup>2</sup>
Switched	No
Twin Earth Terminals	No
Ingress Protection	IP20
Back Box Depth	25mm Minimum
Termination Type	Screw
Operational Temperature	-5°C to +40°C
Warranty	10 Years

**Standards** BS 546: 1950

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.