

Technical Specification

Product Code: CMA147PL



3 Apertures



General Information

Dimensions 146mm (W) x 86mm (H) x 9.5mm (D)

Material Composition Front Plate & Control Button: Urea

Fixing Centres 120.6mm

Terminal Size Dependent On Modules Fitted

Terminal Torque Dependent On Modules Fitted
Terminal Capacity Dependent On Modules Fitted

Control Type Dependant On Module(s) Installed
Back Box Depth Dependent On Modules Fitted

Temperature Rating -5°C to +40°C
Warranty 20 Years

Standards BS 5733: 2010 +A1: 2014

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested and achieved a 99.9% kill rate across all four types of

the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Interchangeable with dimmer modules in the MiniGrid Range. Suitable for dimmer modules with M10 thread, 25mm wide housing.

Interchangeable Modules MD9014: 100W Dual Mode LED Dimmer Module

MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module

MD9010: 1-10V Analogue Rotary Dimmer Module MD9022: 40-250W Leading Edge Dimmer Module MD9042: 60-400W Leading Edge Dimmer Module



