

## **Technical Specification**



Product Code: MD022PW-MW Description: 20A Double Pole Switch Module





## **General Information**

 $\label{eq:definition} \textbf{Dimensions} \qquad 41 \text{mm (W)} \ \text{x} \ 52.5 \text{mm (H)} \ \text{x} \ 22 \text{mm (D)}$ 

Aperture Dimensions 32mm (W) x 31.5mm (H)

Finish Polar White

Materials Rocker Switch: Urea

Rear Housing: Nylon Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Maximum Voltage 250V 50Hz

Load Rating 20A
Terminal Size 4.4mmø
Terminal Torque 1.2Nm

**Terminal Capacity** 4 x 1.5mm<sup>2</sup> or 2 x 2.5mm<sup>2</sup>

Product Markings Microwave

Back Box Depth Dependent On Plate Used

Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges