

## **Technical Specification**

CLICK® ScolmoreGROUP

Product Code: VPBR423 Description: 10AX 3 Gang 2 Way Toggle Plate Switch





Representative Image

## **General Information**

Dimensions 146mm (W) x 88mm (H) x 8mm (D)

Dimensions With Gasket 149mm (W) x 91mm (H) x 9mm (D)

Plate Design & Finish Victorian Polished Brass

Gasket Colour Supplied With Both Black & White Gasket

Switch Finish Polished Brass

Materials Front Plate: Stainless Steel

Switch Front & Nut: Cast Zinc

Rear Housing: Nylon Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Gasket: Nylon

 $\textbf{Maximum Voltage} \qquad 250 \text{V}{\sim} \ 50 \text{Hz}$ 

Load Rating 10AX (Suitable for Inductive Loads)

Plate Fixing Centres 120.6mm

**Terminal Size** 4.9mm x 4.1mm

**Terminal Torque** 1.2Nm

**Terminal Capacity** 4 x 1.5mm² or 2 x 2.5mm²

Two Way Yes

Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

## **Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. Intermediate toggle switches modules are available which interchange with the modules fitted. Order

MD9125BR for polished brass finish.