


Product Code: PRW105

Description: 10AX 6 Gang 2 Way Plate Switch



### General Information

Dimensions	146mm (W) x 86mm (H) x 11mm (D)
Plate Design & Finish	Square Edge Polar White
Materials	Front Plate & Rocker Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass
Maximum Voltage	250V~ 50Hz
Load Rating	10AX (Suitable for Inductive Loads)
Plate Fixing Centres	120.6mm
Terminal Size	3.5mmø
Terminal Torque	0.5Nm
Terminal Capacity	4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>
Two Way	Yes
Ingress Protection	IP20
Back Box Depth	16mm Minimum
Termination Type	Screw
Operational Temperature	-5°C to +40°C
Warranty	20 Years
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases.  
All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.  
Interchangeable with modules in the MiniGrid Range.