

Technical Specification

Product Code: MD022SC-HB

Description: 20A Double Pole Switch Module





General Information

| | , |
|-------------------------|--|
| Additional Information | Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. |
| Standards | BS EN 60669-1:1999 +A1:2002 +A2:2008 |
| Warranty | 10 Years |
| Operational Temperature | -5°C to +40°C |
| Back Box Depth | Dependent On Plate Used |
| Product Markings | Hob |
| Terminal Capacity | 4 x 1.5mm ² or 2 x 2.5mm ² |
| Terminal Torque | 1.2Nm |
| Terminal Size | 4.4mmø |
| Load Rating | 20A |
| Maximum Voltage | 250V 50Hz |
| Materials | Rocker Switch: Urea Rear Housing: Nylon Switch Cover: Stainless Steel Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass |
| Finish | Satin Chrome |
| Aperture Dimensions | 32mm (W) x 31.5mm (H) |
| Dimensions | 41mm (W) x 52.5mm (H) x 22mm (D) |

UK Design Registration: 3015621