


Product Code: FPBS038WH

Description: 5A Round Pin Socket Outlet



Representative Image

General Information

| | |
|-------------------------|--|
| Dimensions | 86mm (W) x 86mm (H) x 1.3mm (D) |
| Dimensions With Gasket | 86mm (W) x 86mm (H) x 3mm (D) |
| Plate Design & Finish | Flat Plate Brushed Stainless |
| Insert Colour | White |
| Materials | Front Plate: Stainless Steel Insert: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel |
| Maximum Voltage | 250V~ 50Hz |
| Load Rating | 5A |
| Plate Fixing Centres | 60.3mm |
| Terminal Size | 5mmø |
| Terminal Torque | 1.2Nm |
| Terminal Capacity | 4 x 1.5mm ² or 3 x 2.5mm ² |
| Switched | No |
| Twin Earth Terminals | No |
| Ingress Protection | IP20 |
| Back Box Depth | 25mm Minimum |
| Operational Temperature | -5°C to +40°C |
| Warranty | 10 Years |

Standards BS 546: 1950

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.