

Product Code: FPBN422

Description: 10AX 2 Gang 2 Way Toggle Plate Switch



Representative Image

### General Information

Dimensions	86mm (W) x 86mm (H) x 1.3mm (D)
Dimensions With Gasket	86mm (W) x 86mm (H) x 3mm (D)
Plate Design & Finish	Flat Plate Black Nickel
Switch Finish	Black Nickel
Materials	Front Plate: Stainless Steel Switch Front & Nut: Cast Zinc Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	10AX (Suitable for Inductive Loads)
Plate Fixing Centres	60.3mm
Terminal Size	4.9mm x 4.1mm
Terminal Torque	1.2Nm
Terminal Capacity	4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>
Two Way	Yes
Ingress Protection	IP20
Back Box Depth	35mm Minimum
Operational Temperature	-5°C to +40°C
Warranty	10 Years

**Standards** BS EN 60669-1:1999 +A1:2002 +A2:2008

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Intermediate toggle switches modules are available which interchange with the modules fitted. Order MD9125BN for black nickel finish.