


Technical Specification



Product Code: SIN504BKSS

Description: 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket Outlet Insert





Representative Image

General Information

Dimensions	142.5mm (W) x 82.5mm (H) x 2.5mm (D)
Insert Finish	Black Insert With Stainless Steel Switches
Cover Plate Finishes Available	BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar White)
Materials	Insert: Polycarbonate Rear Housing: Urea Switch Cover: Stainless Steel Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	45A
Plate Fixing Centres	120.6mm (Vertical Fixing)
Terminal Size	6mmø
Terminal Torque	2.5Nm
Terminal Capacity	1 x 16mm ²
Double Pole	Yes
Twin Earth Terminals	Yes
Neon Indicator	Yes (Red)
Ingress Protection	IP20
Back Box Depth	47mm
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS 4177:1992
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Page 1 of 2 Rev.1.3 Errors & Omissions excluded. Specification is subject to change without notice.



Technical Specification



Product Code: SIN504BKSS

Description: 45A Ingot 2 Gang Double Pole Switch With 13A Double Pole Switched Socket Outlet Insert

Compatible Cover Plates

Plate Dimensions	146mm (W) x 86mm (H) x 4mm (D)
Cover Plate Finishes Available	BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar White)
Materials:	Decorative: Stainless Steel, Black & Polar White: Polycarbonate



