

Product Code: SIN204PW

Technical Specification

Description: 45A 2 Gang Double Pole Switch With 13A Double Pole Switched Socket

Dutlet Insert





Representative Image

General Information

Dimensions 142.5mm (W) x 82.5mm (H) x 2.5mm (D)

Insert Finish Polar White Insert & Switches

Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar

White)

Materials Insert: Polycarbonate

Switch & Rear Housing: Urea

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 45A

Plate Fixing Centres 120.6mm
Terminal Size 6mmø
Terminal Torque 2.5Nm
Terminal Capacity 1 x 16mm²

Double Pole Yes
Twin Earth Terminals Yes
Ingress Protection IP20
Back Box Depth 47mm

Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 4177:1992

Additional Information Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Technical Specification



Product Code: SIN204PW Description: 45A 2 Gang Double Pole Switch With 13A Double Pole Switched Socket

Outlet Inser

Compatible Cover Plates

Plate Dimensions 146mm (W) x 86mm (H) x 4mm (D)


Cover Plate Finishes Available BS (Brushed Stainless), CH (Polished Chrome), SS (Stainless Steel), BK (Matt Black) & PW (Polar

White)

Materials: Decorative: Stainless Steel, Black & Polar White: Polycarbonate







SCP204BS SCP204CH SCP204SS





SCP204BK SCP204PW