

Technical Specification

Product Code: PRW032

Description: 13A 2 Gang Unswitched Socket Outlet



General Information

Dimensions 146mm (W) x 86mm (H) x 11mm (D) Plate Design & Finish Square Edge Polar White Materials Front Plate: Urea Rear Housing: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel 250V~ 50Hz Maximum Voltage Load Rating 13A **Plate Fixing Centres** 120.6mm **Terminal Size** 5mmø **Terminal Torque** 2.5Nm **Terminal Capacity** 4 x 2.5mm² **Twin Earth Terminals** Yes **Ingress Protection** IP20 Back Box Depth 25mm Minimum **Operational Temperature** -5°C to +40°C Warranty 20 Years Standards BS 1363-2: 2016 +A1: 2018 **Additional Information** Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.