

## **Technical Specification**

CLICK® ScolmoreGROUP

Product Code: FPBS038BK Description: 5A Round Pin Socket Outlet





Representative Image

## **General Information**

 $\begin{array}{ccc} \textbf{Dimensions} & & 86\text{mm (W)} \times 86\text{mm (H)} \times 1.3\text{mm (D)} \\ \textbf{Dimensions With Gasket} & & 86\text{mm (W)} \times 86\text{mm (H)} \times 3\text{mm (D)} \\ \end{array}$ 

Plate Design & Finish Flat Plate Brushed Stainless

Insert Colour Black

Materials Front Plate: Stainless Steel

Insert: Urea

Rear Housing: Nylon Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V∼ 50Hz

Load Rating 5A
Plate Fixing Centres 60.3mm
Terminal Size 5mmø
Terminal Torque 1.2Nm

**Terminal Capacity** 4 x 1.5mm<sup>2</sup> or 3 x 2.5mm<sup>2</sup>

Switched No
Twin Earth Terminals No
Ingress Protection IP20

Back Box Depth 25mm Minimum
Operational Temperature -5°C to +40°C

Warranty 10 Years

Standards BS 546: 1950

Additional Information Ensure that th

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.