

Product Code: MD018WH-MW

Description: 13A/10AX Double Pole Switch Module



General Information

| | |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions | 25mm (W) x 53mm (H) x 20mm (D) |
| Aperture Dimensions | 16mm (W) x 31.5mm (H) |
| Finish | Click White |
| Materials | Rocker Switch: Urea Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass |
| Maximum Voltage | 250V 50Hz |
| Load Rating | 13A/10AX (Suitable For Inductive Loads) |
| Terminal Size | 3.5mmø |
| Terminal Torque | 0.4Nm |
| Terminal Capacity | 4 x 1.5mm ² or 2 x 2.5mm ² |
| Product Markings | Microwave |
| Back Box Depth | Dependent On Plate Used |
| Operational Temperature | -5°C to +40°C |
| Warranty | 10 Years |
| Standards | BS EN 60669-1:1999 +A1:2002 +A2:2008 |

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Suitable and matches both the Deco white range and Metal Clad range.