

## **Technical Specification**



Product Code: DPBR536BK Description: 13A Ingot 2 Gang Double Pole Switched Socket Outlet





Representative Image

## **General Information**

**Dimensions** 146mm (W) x 88mm (H) x 8mm (D)

**Dimensions With Gasket** 149mm (W) x 91mm (H) x 9mm (D) Rounded Profile Polished Brass

Plate Design & Finish Insert & Gasket Colour

Black

Materials Front Plate: Stainless Steel Insert & Housing: Urea

Switch Cover: Stainless Steel

Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Maximum Voltage 250V~ 50Hz

Load Rating 13A Plate Fixing Centres 120.6mm Terminal Size 5mmø

**Terminal Torque** 2.5Nm

**Terminal Capacity** 4 x 2.5mm<sup>2</sup> or 2 x 4mm<sup>2</sup>

Double Pole Yes Twin Earth Terminals Yes **Ingress Protection** IP20

25mm Minimum Back Box Depth Operational Temperature  $-5^{\circ}C$  to  $+40^{\circ}C$ 

> Warranty 10 Years

**Standards** BS 1363-2: 2016 +A1: 2018

## **Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.