

Product Code: CL036

Description: 13A 2 Gang Double Pole Switched Socket Outlet



General Information

Dimensions	140mm (W) x 80mm (H) x 42mm (D)
Finish	Metal Clad Grey
Materials	Front Plate & Pattress Box: Electrophoretically Coated Steel Insert & Rocker Switch: Urea Rear Housing: Urea Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz
Load Rating	13A
Plate Fixing Centres	120.6mm
Terminal Size	5mmø
Terminal Torque	2.5Nm
Terminal Capacity	4 x 2.5mm ² , 2 x 4mm ²
Double Pole	Yes
Twin Earth Terminals	Yes
Back Box Depth	40mm Supplied
Earth Terminal Provided	Yes
Back Box Knockouts	7 x 20mm (3 on top, 2 on bottom, 1 on each side)
Operational Temperature	-5°C to +40°C
Warranty	10 Years
Standards	BS 1363-2: 2016 +A1: 2018

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.