

Product Code: FPSS422

Description: 10AX 2 Gang 2 Way Toggle Plate Switch



Representative Image

**General Information**

<b>Dimensions</b>	86mm (W) x 86mm (H) x 1.3mm (D)
<b>Dimensions With Gasket</b>	86mm (W) x 86mm (H) x 3mm (D)
<b>Plate Design &amp; Finish</b>	Flat Plate Stainless Steel
<b>Switch Finish</b>	Pearl Nickel
<b>Materials</b>	Front Plate: Stainless Steel Switch Front & Nut: Cast Zinc Rear Housing: Nylon Terminals: Brass Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass Earth Strap: Mild Steel
<b>Maximum Voltage</b>	250V~ 50Hz
<b>Load Rating</b>	10AX (Suitable for Inductive Loads)
<b>Plate Fixing Centres</b>	60.3mm
<b>Terminal Size</b>	4.9mm x 4.1mm
<b>Terminal Torque</b>	1.2Nm
<b>Terminal Capacity</b>	4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>
<b>Two Way</b>	Yes
<b>Ingress Protection</b>	IP20
<b>Back Box Depth</b>	35mm Minimum
<b>Operational Temperature</b>	-5°C to +40°C
<b>Warranty</b>	10 Years

**Standards**

BS EN 60669-1:1999 +A1:2002 +A2:2008

**Additional Information**

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Intermediate toggle switches modules are available which interchange with the modules fitted. Order MD9125PN for pearl nickel finish.