

Technical Specification



Product Code: CMA200 Description: 45A 1 Gang Double Pole Plate Switch





General Information

Material Composition Front Plate & Rocker Switch: Urea

Rear Housing: Urea Terminals: Brass

Terminal Screws: Steel & Yellow Passivated Contacts: Silver "on-lay" Copper / Brass Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

 $\begin{tabular}{lll} \textbf{Maximum Voltage} & 250V \sim 50 \text{Hz} \\ \hline \textbf{Fixing Centres} & 60.3 \text{mm} \\ \hline \textbf{Terminal Size} & 6 \text{mmø} \\ \hline \textbf{Terminal Torque} & 2.5 \text{Nm} \\ \hline \textbf{Terminal Capacity} & 1 \times 16 \text{mm}^2 \\ \hline \end{tabular}$

Double Pole Yes
Twin Earth Terminals Yes

Back Box Depth 35mm Minimum
Temperature Rating -5°C to +40°C
Warranty 20 Years

Standards BS EN 60669-1:1999 +A1:2002 +A2:2008

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal. All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products have been independently tested and achieved a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

