



3 Year Warranty

L70 25,000hrs

Triac dimmable as standard

Emergency option

White, Matt White, Polished
Chrome & Satin Nickel
bezel finish options



EN-DE5
(H) 69mm Height
(OD) 78mm Overall (Ø)

EN-DE52
(H) 90mm Height
(OD) 88mm Overall (Ø)



LED Fixed/Adjustable Fire Rated Downlights

Sparkling, low glare, multifaceted EnFiniti™ lens

Delivering up to 98lm/W

Slim, interchangeable IP65 bezels (fixed version) provide a sleek finish

IP20 bezel included for adjustable

Integrated driver with new push fit loop in/out terminals suitable for use with solid or stranded cable for easy installation

Fibre based insulation coverable - up to 300mm

60° beam angle for uniform light distribution

Tested in 30, 60 and 90 minute solid timber joist fire rated ceilings†

make smart with



See pg.256-258 for compatibility table



Fixed IP65



Adjustable



AIR leakage (excluding adjustable)

Cat. No. Watts Colour Lumens lm/W Beam Cutout [Ø]

E5™ Triac Dimmable Fixed (IP65 when used with IP65 Bezel)

EN-DE5/30 4.5W 3000K 400lm 89 60° 65mm

EN-DE5/40 4.5W 4000K 420lm 93 60° 65mm

E5™ Triac Dimmable Adjustable

EN-DE52*30 4.5W 3000K 420lm 93 60° 75mm

EN-DE52*40 4.5W 4000K 440lm 98 60° 75mm

Accessories

EN-BZE5* E5™ Fixed IP65 Aluminium Downlight Bezel

*Add suffix **W**, **MW**, **PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes. 3 hour Emergency pack AU-FRLM10EM available.

†Suitable for use in 30 minute i-joist fire rated ceilings. See pg.262

