

Ordering information

Plastic enclosed switch-disconnectors

OTP16B_, OTP25B_, OTP32B_
S00760A



4-pole front operated switch-disconnectors

Plastic enclosed, IP65, red-yellow

OTP45_, OTP63_
S00761A



OTP125BA4M
S02076A



OTP125BA4B
S00763A



OTP125BA4U
S00773A



OT160_...800_
S01765A



Rated operational current [A]	Cable outlets/ side	Enclosure size [mm]			Type	Order number	Weight [kg]
		W	H	D			
AC22A	AC23A						
≤690V	≤415V						

Includes selector-type red-yellow handle (I-0 and ON-OFF indication), N- and PE-terminals.

Threaded knock-outs, compression glands have to be ordered separately.

16	16	2xM25+M16	130	150	60	OTP16BA4M	1SCA022459R6510	0.5
16	16	2xPg21+Pg11	130	150	60	OTP16BA4P	1SCA022401R4080	0.5
25	20	2xM25+M16	130	150	60	OTP25BA4M	1SCA022459R6600	0.8
25	20	2xPg21+Pg11	130	150	60	OTP25BA4P	1SCA022433R8140	0.8
40	23	2xM25+M16	130	150	60	OTP32BA4M	1SCA022459R6780	0.8
40	23	2xPg21+Pg11	130	150	60	OTP32BA4P	1SCA022433R8220	0.8
63	45	2xM32+M16	145	200	90	OTP45BA4M	1SCA022459R6860	1.0
63	45	2xPg29+Pg11	145	200	90	OTP45BA4P	1SCA022571R5080	1.0
80	63	2xM32+M16	145	200	90	OTP63BA4M	1SCA022459R6940	1.0
80	63	2xPg29+Pg11	145	200	90	OTP63BA4P	1SCA022571R5160	1.0
125	90	2xM50+M16	200	400	140	OTP125BA4M	1SCA022812R7510	2.5

Includes selector-type red-yellow handle (I-0 and ON-OFF indication), N- and PE-terminals.

Knock-out flanges, flanges have to be ordered separately.

125	90	I-flange	200	400	140	OTP125BA4B	1SCA022571R8510	2.5
125	90	-	200	400	140	OTP125BA4U	1SCA022459R7160	2.5

Includes pistol-type red-yellow handle (I-0 and ON-OFF indication), N- and PE-terminals.

Knock-out flanges, flanges have to be ordered separately.

160	135	II-flange	280	380	130	OT160EFCC4BA	1SCA022833R6690	5.4
200	200	II-flange	280	560	180	OT200KFCC4BA	1SCA022834R0530	9.0
250	250	II-flange	280	560	180	OT250KFCC4BA	1SCA022834R0610	9.0
315	315	II-flange	380	560	180	OT315KFCC4BA	1SCA022834R0700	9.0
400	400	II-flange	380	840	180	OT400DFCC4BA	1SCA022834R0880	16.0
570	570	II-flange	380	840	180	OT630KFCC4BA	1SCA022834R1000	20.0
720	720	2xII-flange	560	760	250	OT800KFCC4BA	1SCA022834R1180	30.0